

General Data

IADC Code	M232
Body material	Matrix

Design Specifications

Profile	1	Shallow Cone, Short Profile Length		
Total Cutter Count	54			
Blade count	8			
Cutter distribution	10 mm	13 mm		
- Face	38	2		
- Gauge	14	0		

	Value	Unit	Value	Unit
Ports	8			
Junk Slot Area	5.93	sq. inches	3,825.80	sq. mm
API Connection				
Gauge length	3.00	inches	76.20	mm
Make-Up Length	5.26	inches	133.60	mm

Features

Port configuration	Configuration (1)	: 8 X 14/32"
--------------------	-------------------	--------------

Operating Parameters

Rotary speed	Suitable for RSS or PDM			
H.S.I.	1 to 4			
Weight on bit	4,000 to 28,000	lb	2 to 13	T
Flow rate	150 to 400	gpm	682 to 1,818	lpm
Make Up Torque	18,500 to 20,000	ft lb	2,508 to 2,712	daN m

The above operating parameters are general parameters, please contact your local Tercel representative for recommendations that are specific for your well.

Special Features

TSP PROTECTION ON OD

Comments

Pictures for illustration purposes only
Final product may vary slightly

For more information

Visit www.terceloilfield.com or contact your local sales office

Domestic and international patents and trademarks granted and/or applied for where applicable

THIS DOCUMENT AND THE INFORMATION IN IT ARE PROVIDED IN STRICT CONFIDENCE, FOR THE SOLE PURPOSE OF PROVIDING SPECIFICATIONS OF TERCEL'S PRODUCTS TO TERCEL'S CUSTOMERS AND MAY NOT BE DISCLOSED TO ANY THIRD PARTY OR USED FOR ANY OTHER PURPOSE WITHOUT THE EXPRESS WRITTEN PERMISSION OF TERCEL OILFIELD PRODUCTS LIMITED.